

# RE-GVD

## GSM VOICE DIALER

### General

GSM Voice Dialer sends the preconfigured SMS and Voice message to the registered mobile numbers. The GSM Voice dialer has 2 trigger Inputs and if anyone detects short-circuit, immediately GSM Voice Dialer sends the preconfigured text message and voice message automatically to stored 10 Mobile number.

### Features

- Configuration is done by Android Application Software.
- 2G/3G/4G Micro SIM Card for Voice call and SMS alert.
- 2 trigger inputs.
- Preconfigured voice call & SMS alert.
- Up to 10 Mobile no's configured.
- 1 Relay output.



### Specification

Electrical Specification	
<b>Operating Voltage</b>	24 VDC
<b>Standby Current</b>	20mA Max.
<b>Trigger Current</b>	100mA Max.
<b>Operating Temperature</b>	0°C to 55°C.
<b>Relative Humidity</b>	93 ± 2% RH (non-condensing) at 32 ± 2° C / 90 ± 3° F.
<b>SIM Card</b>	Micro SIM.
<b>Enclosure</b>	Sheet Metal.
<b>Weight</b>	200g.
<b>Size</b>	85H x 105L x 35D in mm.
<b>Mounting</b>	Din Rail / Wall Mount.

### Ordering Information

Models	Description
RE-GVD	GSM Voice Dialer

#### India

RAVEL ELECTRONICS PVT LTD.,  
150A, Electronics Industrial Estate,  
Perungudi, Chennai – 96, India.  
E-mail: [marketing@ravelfire.com](mailto:marketing@ravelfire.com); Web: [www.ravelfire.com](http://www.ravelfire.com)

\*Ravel reserve the right to change the specification without prior notice.

#### USA

RAVEL AMERICAS INC.,  
2855 NW 112<sup>th</sup> Ave ST#2 Miami,  
Doral, Florida 33172, USA.